



## AUTO WASH 60

Low VOC High Flash Automatic Press Wash

### Description:

A high flash point/lower VOC press wash to be used on all types of sheetfed and web press equipment. AUTO WASH 60 contains a mixture of solvents that provide excellent ink cutting power and components that help remove paper coating and fibers. AUTO WASH 60 is emulsifiable with water to help in the removal of water soluble contaminants.

### Directions for Use:

**By Hand:** Blankets – Apply a liberal amount of AUTO WASH 60 to a clean rag and wipe across blanket surface until ink and paper contaminants are removed. Follow-up with a water rinse to remove any residue.

**Rollers:** Apply enough wash to thoroughly clean ink from all rollers. Follow-up with water rinse to remove any residue.

**Automatic Blanket & Roller Washes:** Follow manufacturers' instructions for use in automatic wash equipment. Add water for faster drying and better removal of paper coating and fiber.

### Specifications:

Appearance	: Clear colourless liquid
Specific Gravity	: 0.8 @ 20°C
Boiling Range	: 175°C to 205°C
Flash Point	: 60°C

## Kapoor Imaging Pvt. Ltd.

3, Masilamani Road, Balaji Nagar, Royapettah  
Chennai - 600 014, INDIA  
Phone : +91 44 4347 1000, Fax : +91 44 4347 1020  
Email : sales@kapoorimaging.com  
Website : www.kapoorimaging.com

Distributor