



TOPAZ



TZPSA-H

Pressure sensitive Adhesive for Automatic Application

Description:

Topaz TZPSA-H is premium grade Pressure sensitive adhesive based on polyvinyl acetate terpolymers dispersion in water having very good tack & excellent adhesives cohesive strength.

Characteristics:

Appearance	: Milky White Emulsion
Solid contents	: 54 - 56%
Brookfield Viscosity	: 3000 - 8000 cPs
RVDV-E Sp 5/20 @ 30°C	
pH	: 4 - 6
Film Properties	: Transparent
Specific Gravity@ 30°C	: 1.05 to 1.1

Applications:

Topaz TZPSA-H has good flow, wetting ability and excellent tack. The dispersion is mainly suitable for both machines application process & Manual

application process. Labels made with Topaz TZPSA-H Exhibits least transfer of adhesives on the substrate where the sticker is applied, Topaz TZPSA-H is used for preparation of sticker for labeling HDPE, LDPE, PET & PVC bottles containers.

Storage & Handling:

Topaz TZPSA-H can be stored in poly lined or SS containers. To have a longer shelf life the container should be kept tightly closed in cool but frost free place. The product can be easily washed off with water before the film dries up. In some case warm water with little scrubbing is required. In the event of the product coming in the direct contact with eyes or skin washing with plenty of water should be restored. For any abnormal symptoms seek medical advice.

Stability: Topaz TZPSA-H has a long shelf life of 6 month provided it is stored in cool place.

Packing: Topaz TZPSA-H is available in 50 Kg & 200 Kg.

Kapoor Imaging Pvt. Ltd.

3, Masilamani Road, Balaji Nagar, Royapettah
Chennai - 600 014, INDIA
Phone : +91 44 4347 1000, Fax : +91 44 4347 1020
Email : sales@kapoorimaging.com
Website : www.kapoorimaging.com

Distributor